Detector Variation in c0




Detector Variation in c0
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
c0
Detector
0.0012
0.0010
0.0008
0.0006
0.0004
0.0002
0.0000
−0.0002
0.005
0.000
−0.005
−0.010
−0.015
0.0003
0.0002
0.0001
0.0000
−0.0001
0
5
10
15
20
30
40
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Detector Variation in c0
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
c0
Detector
0.045
0.040
0.035
0.030
0.025
0.020
0.015
0.000
−0.002
−0.004
−0.006
−0.008
−0.010
0.010
0.008
0.006
0.004
0.002
0.000
−0.002
0
5
10
15
20
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

Detector Variation in 1/c1



Detector Variation in 1/c1




Detector Variation in 1/c1
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
1/c1
Detector
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

Detector Variation in c2




Detector Variation in c2
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
c2
Detector
0
−1×10⁻⁹
−2×10⁻⁹
−3×10⁻⁹
−4×10⁻⁹
2.0×10⁻⁸
1.5×10⁻⁸
1.0×10⁻⁸
5.0×10⁻⁹
−1.5×10⁻⁹
−2.0×10⁻⁹
−2.5×10⁻⁹
−3.0×10⁻⁹
−3.5×10⁻⁹
−4×10⁻⁹
−5×10⁻⁹
−6×10⁻⁹
−7×10⁻⁹
0
10
20
30
40
5
15
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Detector Variation in c2
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
c2
Detector
1.4×10⁻⁷
1.2×10⁻⁷
1.0×10⁻⁷
8.0×10⁻⁸
6.0×10⁻⁸
2.4×10⁻⁸
2.2×10⁻⁸
2.0×10⁻⁸
1.8×10⁻⁸
1.6×10⁻⁸
1.4×10⁻⁸
1.2×10⁻⁸
1.0×10⁻⁸
8.0×10⁻⁹
6.0×10⁻⁹
0
5
10
15
20
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

Temperature Variation in c0



Temperature Variation in c0




Temperature Variation in c0
I4 SS1, HAM=A
0.0025
0.0020
0.0015
0.0010
0.0005
0.0000
−0.0005
−0.0010
c0
0
33
Detectors


Temperature Variation in c0
I5 SS1, HAM=A
0.010
0.005
0.000
−0.005
−0.010
−0.015
c0
0
33
Detectors


Temperature Variation in c0
M12 SS1, HAM=A
0.0006
0.0004
0.0002
0.0000
−0.0002
−0.0004
−0.0006
c0
0
17
Detectors


Temperature Variation in c0
M13 SS1, HAM=A
0.0015
0.0010
0.0005
0.0000
−0.0005
−0.0010
c0
0
17
Detectors


Temperature Variation in c0
M14 SS1, HAM=A
0.06
0.05
0.04
0.03
0.02
0.01
c0
0
17
Detectors


Temperature Variation in c0
M15 SS1, HAM=A
0.002
0.000
−0.002
−0.004
−0.006
−0.008
−0.010
−0.012
c0
0
17
Detectors


Temperature Variation in c0
M16A SS1, HAM=A
0.015
0.010
0.005
0.000
−0.005
c0
0
17
Detectors


Temperature Variation in c0
M16B SS1, HAM=A
0.012
0.010
0.008
0.006
0.004
0.002
0.000
−0.002
−0.004
c0
0
17
Detectors

Temperature Variation in c0



Temperature Variation in 1/c1



Temperature Variation in 1/c1



Temperature Variation in 1/c1



Temperature Variation in a2



Temperature Variation in c2



Temperature Variation in c2



dn vs dL_BCS


I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
dn
dL_BCS
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


dn vs dL_BCS
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
dn
dL_BCS
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


dn vs dL_BCS
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
dn
dL_BCS
0
1000
2000
3000
4000
0
5
10
15
20
25
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

Detector Variation in RRCU



Detector Variation in RRCU



Detector Variation in RRCU



Detector Variation in RRCU



Detector Variation in RRCU



Detector Variation in RRCU



Detector Variation in RRNL




Detector Variation in RRNL
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
RRNL
Detector
0.012
0.010
0.008
0.006
0.004
0.002
0.000
0
5
10
15
20
30
40
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Detector Variation in RRNL
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
RRNL
0.012
0.010
0.008
0.006
0.004
0.002
0.000
0
5
10
15
20
Detector
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

ARD vs T_BCS


I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
BCS ARD
T_BCS (K)
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


ARD vs T_BCS
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
BCS ARD
T_BCS [K]
1.0
0.5
0.0
−0.5
220
240
260
280
300
320
340
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


ARD vs T_BCS
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
BCS ARD
T_BCS [K]
1.0
0.5
0.0
−0.5
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

RRU in T_BCS


I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
BCS RRU
T_BCS (K)
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

RRU in T_BCS


I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
BCS RRU
T_BCS [K]
0.0
0.2
0.4
0.6
0.8
1.0
240
260
280
300
320
340
200
250
300
350
220
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

RRU in T_BCS


M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
BCS RRU
T_BCS [K]
0.0
0.2
0.4
0.6
0.8
1.0
220
240
260
280
300
320
340
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

NEdT at Ttyp vs detector




NEdT at Ttyp vs detector
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
NEdT at Ttyp [K]
Detector
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


NEdT at Ttyp vs detector
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
NEdT at Ttyp [K]
Detector
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0
5
10
15
20
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B

NEdT at Ttyp vs T_OMM



NEdT at Ttyp vs T_OMM



NEdT vs T_BCS


I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
NEdT [K]
T_BCS [K]
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


NEdT vs T_BCS
I4 SS1, HAM=A
I5 SS1, HAM=A
M12 SS1, HAM=A
M13 SS1, HAM=A
NEdT [K]
T_BCS [K]
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


NEdT vs T_BCS
M14 SS1, HAM=A
M15 SS1, HAM=A
M16A SS1, HAM=A
M16B SS1, HAM=A
NEdT [K]
T_BCS [K]
0.00
0.05
0.10
0.15
0.20
0.25
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Baseline Percent Error in L_ret vs T_BCS
I4 HAM A
I5 HAM A
M12 HAM A
M13 HAM A
Error (%)
BCS Temperature [K]
1.0
0.8
0.6
0.4
0.2
0.0
220 240 260 280 300 320 340
200 250 300 350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Baseline Percent Error in L_ret vs T_BCS
M14 HAM A
M15 HAM A
M16A HAM A
M16B HAM A
Error (%)
BCS Temperature [K]
1.0
0.8
0.6
0.4
0.2
0.0
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Worst Case Percent Error in L_ret vs T_BCS
I4 HAM A
I5 HAM A
M12 HAM A
M13 HAM A
Error (%)
BCS Temperature [K]
1.0
0.8
0.6
0.4
0.2
0.0
220
240
260
280
300
320
340
200
250
300
350
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B


Worst Case Percent Error in L_ret vs T_BCS
M14 HAM A
M15 HAM A
M16A HAM A
M16B HAM A
Error (%)
1.0
0.8
0.6
0.4
0.2
0.0
200
250
300
350
BCS Temperature [K]
Cold A
Cold B
Nominal A
Nominal B
Hot A
Hot B